



Specification:

60T Heavy duty Low bed Semi-trailer



(THE PICTURE IS ONLY FOR REFERENCE)

The trailer is designed for stevedoring and transporting Military Vehicles and Tank.

Dimension & Weight:

Total Length: 14400mm (Excluding Ladder)

Width: 3280mm

Height:2800mm

Height of Loading Platform: 1350mm

King Pin Location: One positions on 2575mm from the front face of the front bolster

Loading Dimensions: 9500x3280x1350mm

Axle spacer: 6800+1400+1400+1400+1400mm

Tare Weight (Tolerance 0~-4%): approximate 13000kg

Payload:57000kg



中国重汽集团泰安五岳专用汽车有限公司

CHINA NATIONAL HEAVY DUTY TRUCK GROUP TAIAN WUYUE SPECIAL VEHICLE CO.,LTD.

King Pin: . 3.5'' . Made in China

Landing Gear: FW280022S

Suspension: 60T

Axle: Five axle 12000kg class made in China.

Tires: 12.00R22.5, Made in China

Brake System: Dual air brake system, Made in China

Electrical System: 24 volt lighting system,

Front mark light: white ,

Side mark lamp: amber,

Rear lamp: white;

Main structure:HJ58; 490mm deep x 300mm wide x 18mm web welded

I -section main beams. The thickness of top flange is 24mm, the bottom flange is 24mm.

Others:

Spare Tire & Carrier: without spare tire,1 pieces,

Side Guard: None.

Tool Box: one set,

Color of Painting: optional

Marking: sinotrucktrailer standard.

